

nola®



Kaprifol Planter

Design

Wooden barrels make attractive planters, whether combined with a base or placed directly on the ground. Planters have been made in this style for several hundred years, decorating palaces as well as parks. Kaprifol is based on a traditional style found in an eighteenth-century park near Stockholm, and made with traditional wooden staves and metal parts.

CERTIFICATION

Produkt listad i
Svanens Husportal



Dimensions and weight

Diameter of upper rim: Ø 69 cm
Diameter of base: Ø 60 cm
Overall height: 32 cm
Height of upper rim: 11 cm
Weight: 12.8 kg

Planter Top: Ø 65 cm.
Height: 40 cm

Product numbers and combinations

Ö20-32 Underrede till laggkärl.
Ö20-33 Laggkärl.
Ö20-33BT10 Mona bevattningstank, 10lit.

Append to product number

WOOD AND FINISH

EK for oiled oak.

Standard colours

Materials and surface treatments

The planter is made from untreated oak slats with steel straps.

Oak

Oak is a heavy, hard and medium tough wood. Moderately dimensionally stable in case of moisture changes. Oak wood blackens if it is exposed to moisture or wetness for a long time. However, it does not affect the other properties of the wood. Thanks to its hardness and toughness, the oak wood is suitable for furniture and other use in exposed environments.

Wood oil

Wood oil provides good protection against the stresses of the outdoor climate and at the same time highlights the wood's natural appearance and properties.

Recycled sand cast aluminium

Aluminium recycled from scrap, hand cast in sand moulds. The energy consumption when producing recycled aluminium is about 5% of that used when producing virgin aluminium.

Steel

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

Hot-dip galvanized

Hot-dip galvanizing provides very strong protection against corrosion. The steel is dipped into a bath of hot liquid zinc. The zinc attaches and creates a surface coating on the steel part, which is then taken out of the bath and drained of excess zinc.

Assembly and placement

Freestanding

Freestanding product that is placed directly on the ground.

Fully assembled. The planter and base are delivered separately.

Maintenance

Oiled oak

Oiled oak should be oiled twice a year for best protection. Good maintenance can never completely prevent stains from occurring, but oak that is not maintained will turn blacker and turn gray faster, but it still has a very long life. When re-oiling products, a finely boiled oil that penetrates the wood should be chosen over a film-forming oil.

Sand cast aluminium

Maintenance on aluminium is not normally needed, but make sure to wash and keep the material clean. Untreated aluminium develops a matte surface over time.

Hot dip galvanized steel

Hot-dip galvanized can be touch-up painted with so-called "cold galvanizing".

[Read more in our general maintenance advice at nola.se/en/care-and-maintenance](https://nola.se/en/care-and-maintenance)

Versions

/

Character

Kaprifol's design dates back to the eighteenth-century. Today, it continues to be made with traditional wooden staves, steel bands and a cast metal base.