# nola



# Sidewalk Furniture Group

# Design White Arkitekter & Andreas Sture

The Sidewalk furniture group is characterised by clean lines and precise angles that give it a contemporary character. The frames and legs are made from lengths of square steel treated with a silvery finish, complemented by wooden parts that showcase the beauty of painted wood. The seats and tabletop are supported by steel posts that bolt to the ground, creating a stable, immovable base.

## **CERTIFICATION**

Produkt listad i Svanens Husportal BYGGVARU

# **FEATURES**

 $\overset{{}_\circ}{\bigcirc}$  Designed for accessibility

### Dimensions and weight

#### **BACKED BENCH**

Length: 180 cm Depth: 47.5 cm Height: 87.4 cm Seat height: 46 cm Height of

armrest: 68.5 cm Weight: 43.7 kg

### **BENCH**

Length: 180 cm Depth: 40 cm Height: 74 cm Seat height: 46 cm Height of armrest:

68.5 cm Weight: 32 kg

# **TABLE**

Length: 144 cm Depth: 70 cm Weight: 40.5 kg

# Sidewalk Bench

Length: 180 cm Width: 40 cm Sitting height: 46 cm

Weight 32 kg

# Sidewalk Park Bench

Length: 180 cm Height: 87 cm

Armrest height: 68.5 cm Sitting height: 46 cm Depth: 47.5 cm Weight 43,7 kg

#### Sidewalk Table

Length: 144 cm / 72 cm

Width: 70 cm Height: 74 cm

Weight of rectangular table: 40.5 kg Weight of square table: 24 kg

# Sidewalk Chair

Width: 36 cm / 54 cm

Height: 86 cm

Armrest height: 68.5 cm Sitting height: 46 cm

Sitting depth: 45 cm / 47.5 cm Depth: 45 cm / 47.5 cm

Weight of chair / armchair: 12 kg / 18 kg Width of chair / armchair: 36 cm / 54 cm Depth of chair / armchair: 45 cm / 47.5 cm

Height of armrest: 68.5 cm

# Sidewalk barstool

Width: 36 cm Height: 107 cm Sitting height: 80 cm Depth: 45 cm

# Product numbers and combinations

B11-06 Additional fee for choosing a non-standard colour

B11-07 Additional fee for choosing a non-standard colour on wood

U17-04M Sidewalk Bench

U17-04/ARM Sidewalk Bench with armrest

U17-05 Sidewalk Park bench

 U17-05/ARM
 Sidewalk Park bench with armrest

 U17-06
 Sidewalk rectangular table 70 cm x 144 cm

 U17-07
 Sidewalk square table 70 cm x 72 cm

U17-08 Sidewalk Chair

<u>U17-09M</u> <u>Sidewalk Armchair (wider than the chair)</u>

U17-08/BARST Sidewalk barstol

### Append to product number

#### WOOD AND FINISH

SIOO for sioo:x treatment oak.

G for RAL 1023 yellow for topcoated pine.

C for any color other than standard, at additional cost.

#### METAL SURFACE FINISH

Specify color choice for steel when ordering.

RAL 7035 is standard.

C for any color other than standard, at additional cost.

# VARIANTS

PURGS for seat in PUR grey-black NCS 8502-B (bench seat only).

PURGR for seat in PUR green NCS S 8010-G10Y (bench seat only).

Sofa with seat in PUR is delivered with back/armrest in topcoated pine in the same colour.

C for any color other than standard, at additional cost.

### **INSTALLATION TYPE**

N for surface mount.

M for in-ground.

### Standard colours

RAL 7035

RAL 1023

NCS S 8502-B

NCS S 8010-G10Y (Grön)
SiOO:X treatment oak

Materials and surface treatments

#### Pine

Nola's pine is of high quality and comes from sustainable forestry. Pine is an environmentally friendly, domestically produced material. Damaged or untreated pine is quite easily attacked by decomposition processes; therefore, it is particularly important to repair damaged surfaces.

#### Oak

Oak is a heavy, hard and medium tough wood. Moderately dimensionally stable in case of moisture changes. Oak wood blackens if it is exposed to moisture or wetness for a long time. However, it does not affect the other properties of the wood. Thanks to its hardness and toughness, the oak wood is suitable for furniture and other use in exposed environments.

#### **Topcoat**

Painted wood is made with D-Dur Pigmented Polyurethane two-component topcoat. The topcoat has good resistance and outdoor durability. Gloss number: 60.

#### Steel

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

# Plastic / Polyurethane Foam

Polyurethan foam is a highly elastic polymer product and provides a bouncy structure and feels extra comfortable to sit on. With its attributes such as being allergy-neutral, long-lasting and fire- and flame-resistant, it can easily be used in public environments.

### SiOO:X treatment

Sioo:x is a wood protection with environmentally friendly silicon technology. Water-based and biocide-free. We use Sioo mainly for our oak furniture. Sioo:x treatment of is suitable for all woods, outside as well as inside, and gives a light surface without pigments. The surface is UV-resistant, water-repellent and non-stick. Active and preventive action against algae, mould and pests. Also rot-proof, wood-strengthening and fire-retardant. This wood protection provides long durability and easy maintenance.

#### Electrogalvanized

Electrogalvanizing (also known as zinc plating) provides corrosion protection through the sacrifice of zinc ions. It is created via a zinc coating on the steel using an electric current.

### Powder coating

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

Assembly and placement

In-ground

Cast in ground.

#### Surface mount

Can be bolted above ground, to the floor or to a cast-in-place foundation. Bolts not included.

The seat, tabletop and bench surfaces are pre-assembled. The seat requires attachment to the frame.

Maintenance

#### SiOO:X treatment oak

Sioo:x-treated products are treated twice upon delivery; once with a wood protection (Premium Träskydd Altan) and once with a surface protection (Premium Ytskydd Altan). After 12 - 18 months, for best durability, the surface should be treated once more with Sioo:x Premium Ytskydd Altan. It is important to keep the product clean, otherwise the surface protection can be destroyed. Products that are exposed to heavy mechanical wear may need extra treatments. The surface treatment has a tested effect according to the standards EN 46 and EN 113.

For information about the Sioo treatment see the website www.sioox.se.

#### **Topcoat**

Products treated with D-Dur Pigmented polyurethane two-component topcoat should be maintained regularly. Maintenance intervals approx. 1 time per year. Damage and cracks should be repaired immediately. Touch-up paint with, for example, Nordsjö One door and window water-based topcoat.

#### Powdercoated steel

Products that are powder-coated can be touch-up painted with alkyd paint.

Read more in our general maintenance advice at nola.se/en/care-and-maintenance

Versions

Furniture group with sofa, bench, table and chair. Can be adapted based on request.

Character

Characterised by clean lines and precise angles that give it a contemporary character.

Designers

#### White Arkitekter

White Arkitekter is one of Sweden's leading architectural offices. With a focus on sustainable architecture, design and city planning, they aim to work for both the current and future generation. White Arkitekter's aim is to through architecture be able to drive the transition towards a sustainable life.



# **Andreas Sture**

Andreas Sture is a designer at White Architecture where he participates in the process of developing and designing sustainable products.











