

nola®



## Kalmarsund Armchair

Design Lars Gunnars

This robust armchair is made for use in gardens, parks and alongside urban streets. Part of the Kalmarsund furniture suite, the armchair's contemporary shape and sleek profile suit a wide variety of outdoor settings. Placed together, two armchairs create an attractive pair of seats, or can be grouped around a table with several others to form a seating arrangement or dining area. The armchair complements the Kalmarsund benches, which are available in two- or three-seater versions, wall-mounted or freestanding. The armchair's seat, backrest and frame are available in a variety of colours, making it easy to coordinate with a design scheme. The armrests for the armchair and Backed bench are now extended for increased accessibility.

### CERTIFICATION

Produkt listad i  
Svanens Husportal  BYGGGARU  
BEGRÄNNINGEN

## Dimensions and weight

Width: 61 cm  
Height: 84 cm  
Armrest height: 67 cm  
Sitting height: 46 cm  
Depth: 57 cm  
Weight 32 kg

### Individual dimensions

Wood components: Seat and backrest: 30 mm x 95 mm and 30 mm x 120 mm  
Back steel/undercarriage: 50 x 12 mm  
Armrest: 50 x 20 x 2mm  
Diameter of legs: 48 mm x 3.2 mm  
Wall bracket: 50 mm x 10 mm

## Product numbers and combinations

U11-26 Kalmarsund armchair ground-mounted  
U11-27 Kalmarsund armchair attachable version  
B11- Starting cost for powder coating of steel in a color other than standard.  
06 Choose an RAL color  
B11- Starting cost for another color of wood. Choose brown or grey for Linax or  
07 an NCS color for painted wood. If you want the same color on both steel and wood, choose the RAL color for both.

### Append to product number

#### WOOD AND FINISH

MH for oiled mahogany.  
LIN for linax impregnated pine.  
E for oiled oak.  
A for coated pine, light green NCS S 6010-G10Y.  
H for coated pine, maroon NCS S 4550-Y80R.  
GRÅ for coated pine, grey NCS S 5502-B  
C for coated pine any color, starting cost is added.







#### METAL SURFACE FINISH

RAL 9005  
C for any color other than standard, at additional cost.

#### INSTALLATION TYPE

N for surface mount.  
M for in-ground.  
V for mounted to wall.

## Standard colours

 RAL 9005  
 NCS S 6010-G10Y (Grön)  
 NCS S 4550-Y80R (Röd)  
 Oiled oak  
 Oiled mahogany  
 Linax impregnated pine

## Materials and surface treatments

### Pine

Nola's pine is of high quality and comes from sustainable forestry. Pine is an environmentally friendly, domestically produced material. Damaged or untreated pine is quite easily attacked by decomposition processes; therefore, it is particularly important to repair damaged surfaces.

### Mahogany - FSC-certified

FSC-marked mahogany is a wood with good durability in the outdoor environment. In addition, it retains its color tone better than, for example, oak and teak. Mahogany lives and moves, sometimes more than teak.

### Oak

Oak is a heavy, hard and medium tough wood. Moderately dimensionally stable in case of moisture changes. Oak wood blackens if it is exposed to moisture or wetness for a long time. However, it does not affect the other properties of the wood. Thanks to its hardness and toughness, the oak wood is suitable for furniture and other use in exposed environments.

### Oil based glaze

Varnishing of wood is done with a oil-based varnish. Under normal use, the paint has a good wear resistance and long durability.

### Wood oil

Wood oil provides good protection against the stresses of the outdoor climate and at the same time highlights the wood's natural appearance and properties.

### Linax

Linax is a linseed oil-based impregnation that provides extra long durability in outdoor environments and corresponds to impregnation class AB. The impregnated wood turns gray over time, which means that it should be re-oiled if necessary. Use a linseed-based oil for impregnated materials.

After traditional impregnation according to NTR AB, the wood is boiled in a hot linseed oil with or without color pigments under vacuum. The oil is penetrated into the surface on all six sides, which reduces moisture absorption in the wood and gives a dimensionally stable product over time. The result is a dried product with good resistance to rot that also has long maintenance intervals. Linax-impregnated furniture is intended for outdoor environments only.

### Steel

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

### Electrogalvanized

Electrogalvanizing (also known as zinc plating) provides corrosion protection through the sacrifice of zinc ions. It is created via a zinc coating on the steel using an electric current.

### Powder coating

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

## Assembly and placement

**In-ground**

Cast in ground.

**Surface mount**

Can be bolted above ground, to the floor or to a cast-in-place foundation. Bolts not included.

**Mounted to wall**

Bolted in place to stand/wall bracket.

Bolts for walls not included.

Seat and back fully assembled. Legs are delivered separately.

**Maintenance****Oil-based glaze**

Products treated with oil-based topcoat must be maintained regularly with alkyd oil paint. Maintenance intervals approx. 1 time per year. Damage and cracks should be repaired immediately. Paint on spray packaging are available in standard colors to order.

**Oiled oak**

Oiled oak should be oiled twice a year for best protection. Good maintenance can never completely prevent stains from occurring, but oak that is not maintained will turn blacker and turn gray faster, but it still has a very long life. When re-oiling products, a finely boiled oil that penetrates the wood should be chosen over a film-forming oil. Black stains on oiled oak can be removed with oxalic acid.

**Oiled mahogany**

Oiled mahogany should be oiled two times a year.

**Linax impregnated pine**

Outdoor furniture requires oiling every 5 years and panel products and roofs require oiling every 12 years. Maintenance should be done with linseed oil varnish. It is important that the wood is clean and dry (max. 20% moisture content) before it is finished with oil. When washing, do not use high-pressure cleaners. Washing should be done with lukewarm water and then rinsed off with a water hose at normal pressure. Strong grease-dissolving agents should not be used, but washing should be done with a mild household detergent. Detergents containing bleach should also not be used.

The oil can be applied with a roller or brush. Too much oil can cause growth on the wood and give a sticky surface. Attacks by growth can also occur if the wood has not been sufficiently dry or cleaned before the oil is applied. Growth does not damage the wood and is relatively easy to remove, but has a tendency to return.

**Powdercoated steel**

Products that are powder-coated can be touch-up painted with alkyd paint.

**[Read more in our general maintenance advice at nola.se/en/care-and-maintenance](http://nola.se/en/care-and-maintenance)**

**Versions**

Ground-mounted or attached to the surface.

Alkyd enamel on pine or MDF-H.

Oiled teak.

## Character

Part of the Kalmar furniture suite, this contemporary armchair has a sleek profile that complements any urban setting. The armrests are extended for increased accessibility.

## Designers

---

Lars Gunnars

