



Angle Furniture series

Design Synnöve Mork

The Angle furniture series consists of planters in three different sizes and volumes that can be easily combined with complementary benches and trellises. Angle is like an architectural puzzle with almost unlimited possibilities. Together, the pieces can create the most imaginative formations.

Angle can be placed as compartments or create spaces in, for example, parks, on farms or in urban landscapes. The different heights provide the opportunity for varied vegetation, from shrubs to smaller trees. All planters are equipped with three water drainage pipes.

Dimensions and weight

Angle Trellis

Length: 96 cm
Width: 20 cm
Height: 135 cm

Angle Planter

Ö16-76 Large Planter

Length: 140 cm.
Width: Total: 140 cm. Wing: 70 cm.
Diagonal: Length: 197 cm. Width: 148 cm.
Height: 90 cm.
Planter Volume: 1000 Liter.
Weight: 285 kg.

Ö16-77 Medium Planter

Length: 120 cm.
Width: Total: 120 cm. Wing: 60 cm.
Diagonal: Length: 169 cm. Width: 127 cm.
Height: 67,5 cm.
Planter Volume: 550 Liter.
Weight: 192 kg.

Ö16-78 Small Planter

Length: 100 cm.
Width: Total: 100 cm. Wing: 50 cm.
Diagonal: Length: 141 cm. Width: 106 cm.
Height: 45 cm.
Planter Volume: 300 Liter.
Weight: 73 kg.

Angle Bench

Length: 98 cm
Width: 50 cm
Height: 45 cm

Product numbers and combinations

Ö16-74 Angle Trellis

Ö16-76 Angle Planter, 1000 Liters.

Ö16-77 Angle Planter, 550 Liters.

Ö16-78 Angle Planter, 300 Liters.

Ö16-79Ö Angle Bench with open ends

Ö16-79S Angle Bench with closed ends

Append to product number

METAL SURFACE FINISH

C for any color other than standard, starting cost is added.

Standard colours



RAL 6033

RAL 6025



Materials and surface treatments

Steel

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

Zinc powder primer

It's a thermosetting epoxy powder coating primer that can be applied on several type of metal substrates such as aluminium, steel or galvanised steel. This primer has a robust curing window, allowing excellent inter coat adhesion in direct fired ovens and gives very good edge coverage and superior corrosion protection.

Powder coating

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

Maintenance

Powdercoated steel

Products that are powder-coated can be touch-up painted with alkyd paint.

[Read more in our general maintenance advice at \[nola.se/en/care-and-maintenance\]\(https://nola.se/en/care-and-maintenance\)](https://nola.se/en/care-and-maintenance)

Designers

Synnöve Mork

Synnöve Mork showcases a diverse range of creative expressions through her work in design, interior decoration, and exhibition architecture, with textiles being a prominent element. She is renowned for her graphic patterns featuring stripes and squares, which is evident in the Angle planters, her first product for Nola.

