


nola®



Angle Trellis

Design Synnöve Mork

Angle Spaljé is included in the Furniture Series together with planters in three different sizes and volumes that can be easily combined together. The Furniture Series also includes a Bench that together can create the most imaginative formations. Angle as an architectural puzzle with almost unlimited possibilities.



Dimensions and weight

Length: 96 cm
Width: 20 cm
Height: 135 cm

Product numbers and combinations











Ö16-74 Angle Trellis

Append to product number

METAL SURFACE FINISH

C for any color other than standard, starting cost is added.

Standard colours

	RAL 6033
	RAL 6025
	RAL 6028
	RAL 3013
	RAL 5020
	RAL 2002
	RAL 5021
	RAL 7044
	RAL 7048
	RAL 1000

Materials and surface treatments

The trellis is made of powder-coated steel, stainless steel wire and hot-dip galvanized steel feet.

Steel

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

Stainless steel

Stainless steel is an iron alloy with at least 10.5% chromium that often has good resistance to corrosion (rust) and other chemical attacks. A common misconception about stainless steel is that it does not rust at all; it can in fact corrode, especially in environments near the sea with high humidity.

Hot-dip galvanized

Hot-dip galvanizing provides very strong protection against corrosion. The steel is dipped into a bath of hot liquid zinc. The zinc attaches and creates a surface coating on the steel part, which is then taken out of the bath and drained of excess zinc.

Zinc powder primer

It's a thermosetting epoxy powder coating primer that can be applied on several type of metal substrates such as aluminium, steel or galvanised steel. This primer has a robust curing window, allowing excellent inter coat adhesion in direct fired ovens and gives very good edge coverage and superior corrosion protection.

Powder coating

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

Maintenance

Powdercoated steel

Products that are powder-coated can be touch-up painted with alkyd paint.

Hot dip galvanized steel

Hot-dip galvanized can be touch-up painted with so-called "cold galvanizing".

[Read more in our general maintenance advice at nola.se/en/care-and-maintenance](https://nola.se/en/care-and-maintenance)

Designers

Synnöve Mork

Synnöve Mork showcases a diverse range of creative expressions through her work in design, interior decoration, and exhibition architecture, with textiles being a prominent element. She is renowned for her graphic patterns featuring stripes and squares, which is evident in the Angle planters, her first product for Nola.

