# nola




### Duo Bike Stand

### Design Jenny Osuldsen & Snøhetta

Duo's streamlined shape and efficient use of materials results in a uniquely minimalistic style. The bike stand makes a perfect complement to modern architecture, and provides a practical design that urban cyclists can use and appreciate. As the name suggests, Duo provides space for two bicycles, each parked on either side.

CERTIFICATION

® BYGGVARU SUNDAHUS



#### Dimensions and weight

Width: 38 cm Height: 80 cm Weight 14 kg

Base plate: 17 cm x 11 cm

#### Individual dimensions

Manufactured in 12 mm sheet steel

## Product numbers and combinations

Ö60-75 Duo bicycle stand

B11-06 Startup cost for powder coating steel in a color other than standard

#### Append to product number

#### METAL SURFACE FINISH

If nothing is specified after the article number, Duo bollards are in only hot-dip galvanized steel.

S for hot-dip galvanized and powder coated in black RAL 9005.

G for hot-dip galvanized and powder coated in gray Gris 2900 Sablé.


C for any color of steel other than standard, at an additional cost.

#### **INSTALLATION TYPE**

M for installation in pre-cast foundations.

N for surface mount.

#### Standard colours



# Materials and surface treatments

#### Steel

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

#### Hot-dip galvanized

Hot-dip galvanizing provides very strong protection against corrosion. The steel is dipped into a bath of hot liquid zinc. The zinc attaches and creates a surface coating on the steel part, which is then taken out of the bath and drained of excess zinc.

#### Powder coating

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

#### Assembly and placement

#### Surface mount

Can be bolted above ground, to the floor or to a cast-in-place foundation. Bolts not included.

#### Installation in pre-cast foundations

Posts for installation in pre-cast foundations.

Fully assembled

#### Maintenance

#### Powdercoated steel

Products that are powder-coated can be touch-up painted with alkyd paint.

#### Hor dip galvanized steel

Hot-dip galvanized can be touch-up painted with so-called "cold galvanizing".

Read more in our general maintenance advice at nola.se/en/care-and-maintenance

Versions

The product is available with a zinc-electroplated unpainted finish, or zinc-electroplated and powder-coated

Character

Duo was designed by Jenny Osuldsen, an architect at Snøhetta. It complements modern architecture in a practical design that suits many urban bicycle schemes.

#### Designers

#### Jenny Osuldsen & Snøhetta

Jenny B. Osuldsen is partner in Snøhetta and Professor in Landscape Architecture. Educated as Landscape Architect in Norway (MLArch) and in the USA. Joined Snøhetta in 1995 and has had a central position developing the landscape architecture department. She has been deeply involved in many of Snøhetta designs, both in competitions and in a wide range of small and larger projects. She has lectured in several architectural symposia, sharing Snøhetta´s philosophy and design ideas. She is Professor in Landscape Architecture at the University of Life Science in Norway and Guest Professor at Ax:son-Johnson Institute of Sustainable Urban Design SUDes at the University of Lund, Sweden.







