

nola®




Gro Floral Trellis

Design Mia Cullin

A new addition to the Gro planter series that complements the larger freestanding trellis and the medium-sized attachable trellis designed for the rectangular Gro planter. The trellis is compatible with the Gro planter, but can be combined with a range of sizes and shapes not currently offered by the Gro series. On its own, the trellis provides an eye-catching feature that leads creepers and vines upwards along its metal spines. Combined with a planter, the trellis can create a space divider, or provide a subtle means of screening off a larger area. The trellis is unique in its ability to water the plants around it. A discreet water pipe integrated into the frame connects to a watering system that can be placed in the soil beneath it. Designed to be as functional as it is attractive, the Gro trellis encourages growth as it supports the plant life surrounding it.

CERTIFICATION



<p>Dimensions and weight</p>	<p>Height: 96 cm och 116 cm Ø: 50 cm Weight 2,5 kg</p> <p>Thickness: 0.3 cm</p>
<p>Product numbers and combinations</p>	<p>Individual dimensions</p> <p>The trellis and the foot plates are made from 3mm steel plate.</p> <p>The frame is made of pipe Ø15mm x 2 mm.</p> <p>Ö16-04BS Gro floral trellis</p> <p>Append to product number</p> <p>METAL SURFACE FINISH</p> <p>C for any color other than standard, starting cost is added.</p>
<p>Standard colours</p>	<p> RAL 6020</p>
<p>Materials and surface treatments</p>	<p>Zinc plated powder coated steel, painted in RAL 6020. Start-up cost for any RAL colour.</p> <p>Steel</p> <p>Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.</p> <p>Electrogalvanized</p> <p>Electrogalvanizing (also known as zinc plating) provides corrosion protection through the sacrifice of zinc ions. It is created via a zinc coating on the steel using an electric current.</p> <p>Powder coating</p> <p>Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.</p>
<p>Assembly and placement</p>	<p>Freestanding</p> <p>Freestanding product that is placed directly on the ground.</p> <p>Mounted.</p>
<p>Maintenance</p>	<p>Powdercoated steel</p> <p>Products that are powder-coated can be touch-up painted with alkyd paint.</p> <p><u>Read more in our general maintenance advice at nola.se/en/care-and-maintenance</u></p>
<p>Versions</p>	<p>Part of the Gro series of planters.</p>

Character

Elegant and spacious floral trellis.

Designers

Mia Cullin

