


nola®



Halvmåne Ashtray

Design

Elegant ashtray for public use. Easy to empty. Unlock with triangular key, tilt or lift container from bracket. The lid of the container can be tilted when the container is unlocked.

Dimensions and weight	<p>Height: 12 cm</p> <p>Ø: 20 cm</p> <p>Weight 4 kg</p>
Product numbers and combinations	<p>Ö16-73/HM Halvmåne Ashtray with lid, 2 litres. For mounting on a post or wall.</p> <p>Append to product number</p> <p>METAL SURFACE FINISH</p> <p>RAL 9005</p> <p>C for any color other than standard, starting cost is added.</p>
Standard colours	<div>  R AL 9005 </div>
Materials and surface treatments	<p>Steel</p> <p>Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.</p> <p>Hot-dip galvanized</p> <p>Hot-dip galvanizing provides very strong protection against corrosion. The steel is dipped into a bath of hot liquid zinc. The zinc attaches and creates a surface coating on the steel part, which is then taken out of the bath and drained of excess zinc.</p> <p>Powder coating</p> <p>Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.</p>
Assembly and placement	<p>For mounting on a pole or against a wall.</p>
Maintenance	<p>Powdercoated steel</p> <p>Products that are powder-coated can be touch-up painted with alkyd paint.</p> <p>Hot dip galvanized steel</p> <p>Hot-dip galvanized can be touch-up painted with so-called "cold galvanizing".</p> <p><u>Read more in our general maintenance advice at nola.se/en/care-and-maintenance</u></p>