nola



Halvmåne Ashtray

Design

Elegant ashtray for public use. Easy to empty. Unlock with triangular key, tilt or lift container from bracket. The lid of the container can be tilted when the container is unlocked.

Dimensions and weight

Height: 12 cm Ø: 20 cm Weight 4 kg

Product numbers and combinations

Ö16-73/HM Halvmåne Ashtray with lid, 2 litres. For mounting on a post or wall.

Append to product number

METAL SURFACE FINISH

RAL 9005

C for any color other than standard, starting cost is added.

Standard colours

RAL 9005

Materials and surface treatments

Steel

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

Hot-dip galvanized

Hot-dip galvanizing provides very strong protection against corrosion. The steel is dipped into a bath of hot liquid zinc. The zinc attaches and creates a surface coating on the steel part, which is then taken out of the bath and drained of excess zinc.

Powder coating

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

Assembly and placement

For mounting on a pole or against a wall.

Maintenance

Powdercoated steel

Products that are powder-coated can be touch-up painted with alkyd paint.

Hor dip galvanized steel

Hot-dip galvanized can be touch-up painted with so-called "cold galvanizing".

Read more in our general maintenance advice at nola.se/en/care-and-maintenance