# nola



## High Swivel Chair Chair

## Design Mats Aldén

High swivel chair is a modern swivel chair. The idea with the High / Low furniture series is to offer flexible and relaxed furniture for different needs, with a clear design and a clear balance between function and form.


High / Low furniture group is approved in <u>Svanens Husportal</u> and is environmentally assessed via <u>Byggvarubedömningen</u> and <u>SundaHus</u>.

### CERTIFICATION

Produkt listad i Svanens Husportal ® BEDÖMNINGEN SSUNDAHUS

## **FEATURES**

Swivel function



Dimensions and weight

Width: 68 cm med armstöd. 56 cm utan armstöd

Height: 104 cm Sitting height: 46 cm

Depth: 67 cm Weight 50 kg

Product numbers and combinations

U11-59/SNURR High swivel chair

B11-05 Additional fee for choice of non-standard woodB11-06 Additional fee for choice of non-standard colour

Append to product number

WOOD AND FINISH

E for oiled oak.

METAL SURFACE FINISH

 $\boldsymbol{C}$  for any color of steel, at an additional cost. Choose a RAL colour.

**VARIANTS** 

A for Armrests.

INSTALLATION TYPE

N for surface mount.

Standard colours

RAL 3005

RAL 6015

RAL 9005

RAL 9010

Gris 2150 Sablé

Oiled oak

Materials and surface treatments

Powder coated steel in RAL 5021 (Sea blue).

Seat in oiled red oak.

#### Oak

Oak is a heavy, hard and medium tough wood. Moderately dimensionally stable in case of moisture changes. Oak wood blackens if it is exposed to moisture or wetness for a long time. However, it does not affect the other properties of the wood. Thanks to its hardness and toughness, the oak wood is suitable for furniture and other use in exposed environments.

#### Steel

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

#### Wood oil

Wood oil provides good protection against the stresses of the outdoor climate and at the same time highlights the wood's natural appearance and properties.

#### Powder coating

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

#### Electrogalvanized

Electrogalvanizing (also known as zinc plating) provides corrosion protection through the sacrifice of zinc ions. It is created via a zinc coating on the steel using an electric current.

#### Assembly and placement

#### Freestanding

Freestanding product that is placed directly on the ground.

#### Surface mount

Can be bolted above ground, to the floor or to a cast-in-place foundation. Bolts not included.

Partially assembled.

#### Maintenance

#### Oiled oak

Oiled oak should be oiled twice a year for best protection. Good maintenance can never completely prevent stains from occurring, but oak that is not maintained will turn blacker and turn gray faster, but it still has a very long life. When re-oiling products, a finely boiled oil that penetrates the wood should be chosen over a film-forming oil. Black stains on oiled oak can be removed with oxalic acid.

#### Powdercoated steel

Products that are powder-coated can be touch-up painted with alkyd paint.

Read more in our general maintenance advice at nola.se/en/care-and-maintenance

Versions

With or without armrests.

## Character

A swivel chair with a perfect balance between functionality and form. A robust structure create an all-weather ergonomic chair.

## Designers

#### Mats Aldén

Interior and furniture designer, crafter and tutor living in Stockholm. Educated at Aarhus School of Architecture, Denmark. Has his own design studio and workshop in Stockholm since 1995. Has worked as a professor and artistic leader at Steneby HDK, as a lecturer at Konstfack University College of Arts, Crafts & Design and as a guest teacher at Beckmans Design College.

