nola



Kwai Bench

Design Eero Koivisto

This attractive, award-winning indoor bench can create a focal point, yet it is discreet enough to blend into the background. The bench is designed in an elegant expression with slats that taper to thinner widths at the edge. The steel frame slightly lifts the wooden parts and makes the appearance of the bench seem even lighter.

Dimensions	and	weight
------------	-----	--------

Length: 180 cm Width: 40 cm Height: 46 cm Weight 23 kg

Individual dimensions Seat: 10/40 x 192 mm Steel frame: 35 x 15 x 1,5 mm

Product numbers and combinations

U13-30 Kwai benchU13-31 Attachment hardware set of 2B11-06 Startup cost for powder coating steel in a color other than standard.

Append to product number

WOOD AND FINISH

E for oiled oak.

METAL SURFACE FINISH

C for any color other than standard, starting cost is added.

Standard colours



Materials and surface treatments

Oak

Oak is a heavy, hard and medium tough wood. Moderately dimensionally stable in case of moisture changes. Oak wood blackens if it is exposed to moisture or wetness for a long time. However, it does not affect the other properties of the wood. Thanks to its hardness and toughness, the oak wood is suitable for furniture and other use in exposed environments.

Steel

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

Wood oil

Wood oil provides good protection against the stresses of the outdoor climate and at the same time highlights the wood's natural appearance and properties.

Powder coating

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

Assembly and placement

Freestanding

Freestanding product that is placed directly on the ground.

Fully assembled.

Maintenance

Oiled oak

Oiled oak should be oiled twice a year for best protection. Good maintenance can never completely prevent stains from occurring, but oak that is not maintained will turn blacker and turn gray faster, but it still has a very long life. When re-oiling products, a finely boiled oil that penetrates the wood should be chosen over a film-forming oil. Black stains on oiled oak can be removed with oxalic acid.

Powdercoated steel

Products that are powder-coated can be touch-up painted with alkyd paint.

Read more in our general maintenance advice at nola.se/en/care-andmaintenance

Character

A striking bench with immediate appeal, yet discreet enough to blend into the background.

Designers

Eero Koivisto



