nola



Leksand Table

Design Tema

Leksand is renowned for its history of traditional woodworking and timber craftsmanship. The classic Leksand wooden chair dates back to the early 1800s, and provided the inspiration for the armchair, bench and backed bench in this group. The furniture was designed to remain outdoors year-round and meets requirements for accessibility, comfort and durable design. Each product is crafted from FSC-certified cumaro or oak, and fitted with sand-cast aluminium components.


Leksand furniture group has been approved in <u>Svanens Husportal</u> (oiled oak and cumaru) and is assessed via <u>Byggvarubedömningen</u> and <u>SundaHus</u> when choosing oiled oak.

CERTIFICATION

Produkt listad i Svanens Husportal BEGÖMNINGEN SSUNDAHUS

FEATURES

Designed for accessibility



Dimensions and weight

Length: 147 cm Width: 72 cm Height: 74 cm

Length: 147 cm Height: 74 cm Depth: 72 cm

Product numbers and combinations

U16-13 Leksand table

B11-06 Startup cost for powder coating steel in a color other than standard.

Choose a RAL colour.

Append to product number

WOOD AND FINISH

CUM for cumaru.

SIOO for sioo:x treatment oak.

E for oiled oak.

METAL SURFACE FINISH

C for any color other than standard, at additional cost.

INSTALLATION TYPE

N for surface mount.

Standard colours

RAL 7024 Oiled oak

SiOO:X treatment oak

Cumaru

Materials and surface treatments

Seat in untreated Cumaru or oak.

Powder coated in sand cast aluminum in Gray, RAL 7024, fine structure.

Cumaru

Cumaru is sometimes called Brazilian Teak and is a hard and durable type of wood. The wood changes in a red/brown shade and does not need surface treatment thanks to its natural properties. Over the years Cumarun ages in a beautiful silver gray tone.

Oak

Oak is a heavy, hard and medium tough wood. Moderately dimensionally stable in case of moisture changes. Oak wood blackens if it is exposed to moisture or wetness for a long time. However, it does not affect the other properties of the wood. Thanks to its hardness and toughness, the oak wood is suitable for furniture and other use in exposed environments.

Recycled sand cast aluminium

Aluminium recycled from scrap, hand cast in sand moulds. The energy consumption when producing recycled aluminium is about 5% of that used when producing virgin aluminium.

Wood oil

Wood oil provides good protection against the stresses of the outdoor climate and at the same time highlights the wood's natural appearance and properties.

SiOO:X treatment

Sioo:x is a wood protection with environmentally friendly silicon technology. Water-based and biocide-free. We use Sioo mainly for our oak furniture. Sioo:x treatment of is suitable for all woods, outside as well as inside, and gives a light surface without pigments. The surface is UV-resistant, water-repellent and non-stick. Active and preventive action against algae, mould and pests. Also rot-proof, wood-strengthening and fire-retardant. This wood protection provides long durability and easy maintenance.

Powder coating

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

Assembly and placement

Freestanding

Freestanding product that is placed directly on the ground.

Surface mount

Can be bolted above ground, to the floor or to a cast-in-place foundation. Bolts not included.

Fully mounted.

Maintenance

Oiled oak

Oiled oak should be oiled twice a year for best protection. Good maintenance can never completely prevent stains from occurring, but oak that is not maintained will turn blacker and turn gray faster, but it still has a very long life. When re-oiling products, a finely boiled oil that penetrates the wood should be chosen over a film-forming oil. Black stains on oiled oak can be removed with oxalic acid.

SiOO:X treatment oak

Sioo:x-treated products are treated twice upon delivery; once with a wood protection (Premium Träskydd Altan) and once with a surface protection (Premium Ytskydd Altan). After 12 - 18 months, for best durability, the surface should be treated once more with Sioo:x Premium Ytskydd Altan. It is important to keep the product clean, otherwise the surface protection can be destroyed. Products that are exposed to heavy mechanical wear may need extra treatments. The surface treatment has a tested effect according to the standards EN 46 and EN 113.

For information about the Sioo treatment see the website www.sioox.se.

Cumaru

Cumaru shifts in a reddish shade and does not need any maintenance thanks to its natural properties. Over the years Cumaru ages into a beautiful silver gray tone.

Powdercoated steel

Products that are powder-coated can be touch-up painted with alkyd paint.

Read more in our general maintenance advice at nola.se/en/care-and-maintenance

Versions Armchair, bench, table and sofa.

Character Table that combines classic craftsmanship and high quality.

Designers

Tema





