nola



Max Steel Trellis

Design Bernt Fröderberg

Trellises add a decorative touch, whether mounted directly to a structure or erected in the landscape. This wallmounted trellis is designed to enhance buildings as it promotes the growth of trailing vines. It may also be attached to garden walls to add a decorative feature. Crafted in steel, Max encourages the growth of trailing plants up to the top, and even beyond.

Dimensions and weight Product numbers and combinations	Length: 280 cm Width: 55 cm Depth: 37 cm Weight 20 kg Recommended height above ground: 30 cm
	INSTALLATION TYPE V for mounted to wall.
Standard colours	
Materials and surface treatments	 Steel Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated. Hot-dip galvanized Hot-dip galvanizing provides very strong protection against corrosion. The steel is dipped into a bath of hot liquid zinc. The zinc attaches and creates a surface coating on the steel part, which is then taken out of the bath and drained of excess zinc.
	Powder coating Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.
Assembly and placement	Mounted to wall Bolted in place to stand/wall bracket. Bolts for walls not included. Fully assembled.
Maintenance	Not normally required. Hor dip galvanized steel Hot-dip galvanized can be touch-up painted with so-called "cold galvanizing". Read more in our general maintenance advice at nola.se/en/care-and- maintenance
Versions	Available in a choice of three finishes: cold galvanised, hot-dip galvanised and powder-coated in black.

Character

A wall-mounted trellis designed to promote the growth of foliage and trailing vines and provide a decorative garden element.

Designers

Bernt Fröderberg



