

nola®



Minimal Furniture Group

Design

Simple and minimalistic furniture group with room for several people. For staff canteens, study rooms, libraries and other indoor environments. The steel stands are prepared for attachment to the floor. For indoor use only. The bench is available in three different lengths.

Minimal Möbelgrupp is environmentally assessed via [Byggsvarubedömningen](#) and [SundaHus](#) (applies to oiled oak and steel stands).

Can be fireproofed with Protega Novatherm fireproofing, which is a waterborne fireproofing paint, for products which, for example, must be placed in connection with escape routes and entrances.

CERTIFICATION



Can be treated with fire protection

Dimensions and weight

Minimal Bench

Minimal One-seater

Length: 40 cm

Width: 40 cm

Height: 46 cm

Weight: 11 kg

Minimal Two-seater

Length: 80 cm

Width: 40 cm

Height: 46 cm

Weight: 16 kg

Minimal Three-seater

Length: 121 cm

Width: 40 cm

Height: 46 cm

Weight: 21 kg

Material dimensions

Weight of bench with steel frame: 21 kg.

Weight bench in beech: 14 kg.

Seat thickness: 25 mm.

Dimensions of steel frame: 40 mm x 2 mm.

Dimensions of stand in beech 40 x 40 mm.

Minimal table

Length: 121 cm

Width: 70 cm

Height: 70 cm

Vikt: 35 kg

Individual dimensions

Steel frame: 40 mm x 40 mm x 2 mm

Product numbers and combinations

B11-06 Startup cost for powder coating steel in a color other than standard.
Choose a RAL colour.

U13-20 Minimal bench 1-seater, oiled oak, varnished steel frame, indoors

U13-21 Minimal bench 2-seater, oiled oak, varnished steel frame, indoors

U13-22 Minimal bench 3-seater, oiled oak, varnished steel frame, indoors

U13-22A Minimal bench 3-seater with armrests, oiled oak, varnished steel frame, indoors

U13-25 Minimal bench 3-seater, entirely in white-oiled beech tree, indoors

U13-28 Minimal table, oiled oak, varnished steel frame in black, indoors only.

U13-28C Minimal table, oiled oak, varnished steel frame in any color, indoors only.

U13-29B Minimal table, top in white-oiled beech. Varnished steel frame in any color. Indoors only.

Append to product number

WOOD AND FINISH

EK for oiled oak.

METAL SURFACE FINISH

C for optional color for a standard fee.

VARIANTS

Can be treated with fire protection, at additional cost.

For fire protection treatment contact Nola.

INSTALLATION TYPE

N for surface mount.

Standard colours



RAL 9005 finstruktur

Materials and surface treatments

Vitoljad bok.

Oak

Oak is a heavy, hard and medium tough wood. Moderately dimensionally stable in case of moisture changes. Oak wood blackens if it is exposed to moisture or wetness for a long time. However, it does not affect the other properties of the wood. Thanks to its hardness and toughness, the oak wood is suitable for furniture and other use in exposed environments.

Wood oil

Wood oil provides good protection against the stresses of the outdoor climate and at the same time highlights the wood's natural appearance and properties.

Steel

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

Electrogalvanized

Electrogalvanizing (also known as zinc plating) provides corrosion protection through the sacrifice of zinc ions. It is created via a zinc coating on the steel using an electric current.

Powder coating

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

Assembly and placement

Freestanding

Freestanding product that is placed directly on the ground.

Surface mount

Can be bolted above ground, to the floor or to a cast-in-place foundation. Bolts not included.

Levereras färdigmonterad.

Maintenance

Oiled oak

Oiled oak should be oiled twice a year for best protection. Good maintenance can never completely prevent stains from occurring, but oak that is not maintained will turn blacker and turn gray faster, but it still has a very long life. When re-oiling products, a finely boiled oil that penetrates the wood should be chosen over a film-forming oil.

Powdercoated steel

Products that are electro-galvanized and powder-coated can be touch-up painted with alkyd paint.

[Read more in our general maintenance advice at nola.se/en/care-and-maintenance](https://nola.se/en/care-and-maintenance)

Versions

Bänk och bord.

Character

Stilren möbelgrupp för inomhusbruk.

