# nola



## Parklet Modular Urban Spaces

### Design Nola

Making space for the temporary, the imaginary and the unexpected, the multipurpose Parklet system can be installed in a wide variety of environments. Parklet is a unique public space structure that offers a frame for climbing plants while also providing supports for screens, sunshades and rain protection. Parklet can be seen from a distance, creating an architectural way finder that can draw visitors from the entrance to other parts of the site. The structure is also a great choice for children's play areas, pocket parks and urban green areas within the city. Parklet can be repainted, repositioned and extended over time, making it part of a sustainable circular economy with minimal impact on the environment.

#### Dimensions and weight

Length: 2 m Width: 2,4 m Weight 400 kg

Product numbers and combinations

Ö06-30 PARKLET basic module 2000 x 2400 hot-dip galvanized complete with

wood

Ö06-31 PARKLET pergola. 400 cm x 240 cm. 2 sektioner 6 stolpar lackerad -

Lägg till 2 grundmoduler

Standard colours



Materials and surface treatments

#### Steel

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

#### Hot-dip galvanized

Hot-dip galvanizing provides very strong protection against corrosion. The steel is dipped into a bath of hot liquid zinc. The zinc attaches and creates a surface coating on the steel part, which is then taken out of the bath and drained of excess zinc.

#### Pine

Nola's pine is of high quality and comes from sustainable forestry. Pine is an environmentally friendly, domestically produced material. Damaged or untreated pine is quite easily attacked by decomposition processes; therefore, it is particularly important to repair damaged surfaces.

#### SiOO:X treatment

Sioo:x is a wood protection with environmentally friendly silicon technology. Water-based and biocide-free. We use Sioo mainly for our oak furniture. Sioo:x treatment of is suitable for all woods, outside as well as inside, and gives a light surface without pigments. The surface is UV-resistant, water-repellent and non-stick. Active and preventive action against algae, mould and pests. Also rot-proof, wood-strengthening and fire-retardant. This wood protection provides long durability and easy maintenance.

Assembly and placement

Parklet platforms are supplied in ready-made units 2 x 2.4 with assembled timber. Bench is delivered with assembled seat.

Maintenance

#### Hor dip galvanized steel

Hot-dip galvanized can be touch-up painted with so-called "cold galvanizing".

#### SiOO:X treatment on coniferous wood

Sioo:x-treated products are treated twice upon delivery; once with a wood protection (Premium Träskydd Altan) and once with a surface protection (Premium Ytskydd Altan). After 12 - 18 months, for best durability, the surface should be treated once more with Sioo:x Premium Ytskydd Altan. It is important to keep the product clean, otherwise the surface protection can be destroyed. Products that are exposed to heavy mechanical wear may need extra treatments. The surface treatment has a tested effect according to the standards EN 46 and EN 113.

For information about the Sioo treatment see the website www.sioox.se.

Read more in our general maintenance advice at nola.se/en/care-and-maintenance

Versions

Parklet platform, planter and bench

Designers

Nola





Parklet with pergola in red, in the square in the Swedish city of Laholm.









 ${\it Modules with planters. Here with our Sun Chair, designed by Mats Ald\'en.}$