

nola®




Paxa light Table

Design

The Paxa Light table stands on two asymmetrical legs, each balancing the surface weight between them. Crafted in smooth concrete and lightweight steel, the streamlined materials give the table a sleeker appearance than the designs in the original Paxa group. The table is available in sleek steel or with a wooden tabletop supported by steel sides.

FEATURES

 Designed for accessibility

Dimensions and weight

Length: 166 cm
Width: 70 cm
Height: 75 cm

Individual dimensions

Wood components: Seat: 32 x 32 mm och 32 x 60 mm
Steel construction: 10 mm och 4 mm

Product numbers and combinations

U20-78B Paxa Light table 180 cm

B11-05 Additional fee for choice of non-standard wood

B11-06 Additional fee for choice of non-standard RAL paint powder-coated on steel

B11-07 Additional fee for choice of non-standard paint for wooden parts

Append to product number

WOOD AND FINISH

E for oiled oak.

G for glazed pine, dark grey NCS 8502-B.

GB for painted beech, dark grey NCS 8502-B (indoor use only).

C for glazed pine in any choice of colour alt powder-coated frame.

CB for glazed beech in any choice of colour (indoor use only).

C for another color other than standard, starting cost is added.

When choosing painted wood, select an NCS colour. When choosing wood and steel parts in the same colour, choose a RAL colour for both.

METAL SURFACE FINISH

C for another color other than standard, starting cost is added.

INSTALLATION TYPE

N for surface mount.

Standard colours



RAL 9010



NCS S 8502-B



Gris 2900 Sablé



Noir 2200 Sablé



Oiled oak

Materials and surface treatments

Pine

Nola's pine is of high quality and comes from sustainable forestry. Pine is an environmentally friendly, domestically produced material. Damaged or untreated pine is quite easily attacked by decomposition processes; therefore, it is particularly important to repair damaged surfaces.

Beech

The wood of the beech is hard and tough. The wood is striated, which means that the grains are evenly distributed over the entire annual ring. The annual rings are visible, and the wood has an even structure. The color of the wood is yellow, red or brownish-white.

Oak

Oak is a heavy, hard and medium tough wood. Moderately dimensionally stable in case of moisture changes. Oak wood blackens if it is exposed to moisture or wetness for a long time. However, it does not affect the other properties of the wood. Thanks to its hardness and toughness, the oak wood is suitable for furniture and other use in exposed environments.

Steel

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

Wood oil

Wood oil provides good protection against the stresses of the outdoor climate and at the same time highlights the wood's natural appearance and properties.

Water-based glaze

Varnishing of wood is done with a water-based varnish. A water-based paint that is kinder to the environment. Under normal use, the paint has a good wear resistance and long durability.

Electrogalvanized

Electrogalvanizing (also known as zinc plating) provides corrosion protection through the sacrifice of zinc ions. It is created via a zinc coating on the steel using an electric current.

Powder coating

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

Assembly and placement

Freestanding

Freestanding product that is placed directly on the ground.

Surface mount

Can be bolted above ground, to the floor or to a cast-in-place foundation. Bolts not included.

The sides and tabletop are ready for assembly with the bolts included.

Maintenance

Oiled oak

Oiled oak should be oiled twice a year for best protection. Good maintenance can never completely prevent stains from occurring, but oak that is not maintained will turn blacker and turn gray faster, but it still has a very long life. When re-oiling products, a finely boiled oil that penetrates the wood should be chosen over a film-forming oil. Black stains on oiled oak can be removed with oxalic acid.

Water-based glazed pine

Products in varnished pine must be maintained regularly with alkyd paint. Maintenance intervals approximately 1 time per year. Damage and cracks should be repaired immediately. Touch-up paints in spray packaging are available in standard colors to order.

Powdercoated steel

Products that are powder-coated can be touch-up painted with alkyd paint.

[Read more in our general maintenance advice at nola.se/en/care-and-maintenance](https://nola.se/en/care-and-maintenance)

Versions

Also available as a bench.

Character

Stylish, yet robust, this table is suitable for indoor and outdoor environments.