nola




Paxa Table

Design Blenda Design

Part of the Paxa outdoor furniture group, this table stands on two asymmetrical legs, each balancing the surface weight between them. The frame is made in smooth concrete, giving the table a robust appearance. The tabletop is crafted in oiled mahogany, oiled oak or painted pine.

CERTIFICATION

Produkt listad i Svanens Husportal BEDÖMNINGEN



Dimensions and weight Length: 180 cm

Width: 71 cm Height: 76 cm Weight 230 kg

Product numbers and combinations

U20-59 Paxa table

Append to product number

WOOD AND FINISH

E for oiled oak.

MH for oiled mahogany.

G for tabletop in glazed pine. NCS S 6000-N (grey).

C for any NCS color other than standard, starting cost is added.

VARIANTS

A for frame coloured in antracite

No letter after the article number for light grey natural concrete.

INSTALLATION TYPE

M for installation in pre-cast foundations.

Standard colours

NCS S 6000-N (grå)
Infärgad antracitgrå betong
Ljust grå betong ofärgad
Oiled oak
Oiled mahogany

Materials and surface treatments

The frame is made from concrete and hot-dip galvanised steel. The tabletop is available in oiled mahogany, oiled oak or painted pine.

Pine

Nola's pine is of high quality and comes from sustainable forestry. Pine is an environmentally friendly, domestically produced material. Damaged or untreated pine is quite easily attacked by decomposition processes; therefore, it is particularly important to repair damaged surfaces.

Mahogany - FSC-certified

FSC-marked mahogany is a wood with good durability in the outdoor environment. In addition, it retains its color tone better than, for example, oak and teak. Mahogany lives and moves, sometimes more than teak.

Oak

Oak is a heavy, hard and medium tough wood. Moderately dimensionally stable in case of moisture changes. Oak wood blackens if it is exposed to moisture or wetness for a long time. However, it does not affect the other properties of the wood. Thanks to its hardness and toughness, the oak wood is suitable for furniture and other use in exposed environments.

Wood oil

Wood oil provides good protection against the stresses of the outdoor climate and at the same time highlights the wood's natural appearance and properties.

Water-based glaze

Varnishing of wood is done with a water-based varnish. A water-based paint that is kinder to the environment. Under normal use, the paint has a good wear resistance and long durability.

Concrete

Concrete is cement mixed with crushed stone or aggregate. The material is very strong in compression but fragile in tension. To compensate for this concrete can be reinforced, often with steel.

Fiberbetong

Fibre-reinforced concrete is a concrete mix with glass fiber. The material has increased strength and elasticity.

Coloured concrete

Colored concrete is concrete in a color other than standard grey. Pigment is added to the dry mixture, which means that the concrete becomes coloured throughout. Each color has its own recipe.

Assembly and placement

Installation in pre-cast foundations

Posts for installation in pre-cast foundations.

Delivered in parts for assembly on site.

Freestanding or attachable. M16 bolts are required to attach the table to the surface. Bolts are not included.

Maintenance

Damage to concrete can be repaired by using a repair kit, please contact Nola for details.

Oiled oak

Oiled oak should be oiled twice a year for best protection. Good maintenance can never completely prevent stains from occurring, but oak that is not maintained will turn blacker and turn gray faster, but it still has a very long life. When re-oiling products, a finely boiled oil that penetrates the wood should be chosen over a film-forming oil. Black stains on oiled oak can be removed with oxalic acid.

Oiled mahogany

Oiled mahogany should be oiled two times a year.

Water-based glazed pine

Products in varnished pine must be maintained regularly with alkyd paint.

Maintenance intervals approximately 1 time per year. Damage and cracks should be repaired immediately. Touch-up paints in spray packaging are available in standard colors to order.

GRC

Can be cleaned with high-pressure flushing, low water pressure, large distance between nozzle and stone and small flushing angle selected (max. 30°). If the outermost layer of concrete is worn away, the coating will become even more susceptible to impurities in the future. Therefore, cleaning with a brush and water is preferable to the hard abrasion that repeated high-pressure washing entails.

There are also cleaning agents for concrete that has been attacked by dirt and algae and then the concrete can be impregnated, which can also be done when the product is new.

Both normal concrete and fiber concrete are sensitive to hard edge impacts. A concrete product that has been damaged can be repaired with polyester filler, for example the Plastic Padding brand.

Coloured concrete

Products made of coloured concrete are washed with a pressure sprayer at low pressure. Damaged products can be repaired with a repair kit that is available to order.

Read more in our general maintenance advice at nola.se/en/care-and-maintenance

Versions

The concrete frame is available in standard colour grey, or alternatively, anthracite. The tabletop is available in oiled mahogany, oiled oak or pine painted with alkyd oil enamel. Other types of wood are available upon request. The table can be paired with a corresponding bench in the same furniture group.

Examples

Ш

Character

Robust, yet understated, Paxa is perfectly suited to contemporary architecture and modern outdoor environments.

Blenda Design

Blenda is a designstudio based in Gothenburg, committed to designing furniture for public spaces. With design that works towards both interiors and urban exteriors, they have participated in many projects in the recent years. The products can be found across Sweden, for example in Stavanger Cultural Center, Museum of Modern Art in Stockholm, Arlanda Airport and Gothenburg City library. The studio is run by landscape architect Katarina Gunnarsson and Ingemar Holmlid.

