



## Sjöstad Furniture group


Design Erik Österlund

Sjöstad is an example of public space design at its best. This park bench is designed to provide additional support along the armrests and backrest, providing those who need assistance with an independent means of sitting down and standing up. Sjöstad is made to accommodate a wide range of body types and mobilities, making it an efficient combination of contemporary form and ergonomic design. Sjöstad is also available as a bench and a table.

### CERTIFICATION



### FEATURES



Designed for accessibility

## Dimensions and weight

### Individual dimensions

The front legs: 40 mm x 40 mm

The back legs: 40 mm x 50 mm

The sub-frame is made in square pipe: 30 mm x 60 mm

### Sjöstad Park bench

Length: 175 cm

Height: 81 cm

Armrest height: 66 cm

Sitting height: 45 cm

Depth: 55 cm

Weight 45 kg

### Individual dimensions

The front legs: 40 mm x 40 mm

The back legs: 40 mm x 50 mm

The sub-frame is made in square pipe: 30 mm x 60 mm

Back slats: 118 x 32 mm

Seat: Wood components: 92 x 32 mm

### Sjöstad Table

Length: 140 cm

Width: 68 cm

Height: 73 cm

### Individual dimensions

The front legs: 40 mm x 40 mm

The back legs: 40 mm x 50 mm

The sub-frame is made in square pipe: 30 mm x 60 mm

### Sjöstad Bench

Length: 148 cm

Height: 46 cm

Sitting height: 46 cm

Depth: 42 cm

Weight 45 kg

### Individual dimensions

The front legs: 40 mm x 40 mm

The back legs: 40 mm x 50 mm

The sub-frame is made in square pipe: 30 mm x 60 mm

Back slats: 118 x 32 mm

Seat: Wood components: 92 x 32 mm

## Product numbers and combinations

**U20-83** 4 fastening irons, stainless steel

**B11-06** Startup cost for powder coating steel in a color other than standard.  
Choose a RAL colour.

**U20-80** Sjöstad backed bench

**U20-82** Sjöstad table

## U20-81 Sjöstad bänk

### **Append to product number**

#### **WOOD AND FINISH**

E for oiled oak.

MH for oiled mahogany.

A for painted pine in RAL 8028.

#### **METAL SURFACE FINISH**

Gris Sablé 2900 är standard on steel.

C for any color other than standard, starting cost is added.

Choose a RAL colour.

### **Standard colours**



RAL 8028



Gris 2900 Sablé



Oiled oak



Oiled mahogany

### **Materials and surface treatments**

The seat and backrest or made in painted pine in RAL 8028, oiled oak or FSC-mahogany

The sub-frame and all legs are made in square pipe. All steel is zinc-electroplated and powder-coated. All screws are stainless steel. The standard colour is anthracite grey, Gris 900 Sablé.

#### **Pine**

Nola's pine is of high quality and comes from sustainable forestry. Pine is an environmentally friendly, domestically produced material. Damaged or untreated pine is quite easily attacked by decomposition processes; therefore, it is particularly important to repair damaged surfaces.

#### **Mahogany - FSC-certified**

FSC-marked mahogany is a wood with good durability in the outdoor environment. In addition, it retains its color tone better than, for example, oak and teak. Mahogany lives and moves, sometimes more than teak.

#### **Oak**

Oak is a heavy, hard and medium tough wood. Moderately dimensionally stable in case of moisture changes. Oak wood blackens if it is exposed to moisture or wetness for a long time. However, it does not affect the other properties of the wood. Thanks to its hardness and toughness, the oak wood is suitable for furniture and other use in exposed environments.

#### **Wood oil**

Wood oil provides good protection against the stresses of the outdoor climate and at the same time highlights the wood's natural appearance and properties.

#### **Steel**

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

### **Electrogalvanized**

Electrogalvanizing (also known as zinc plating) provides corrosion protection through the sacrifice of zinc ions. It is created via a zinc coating on the steel using an electric current.

### **Powder coating**

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

## **Assembly and placement**

Partly assembled. The seat and backrest should be attached to the frame with enclosed bolts.

## **Maintenance**

### **Oiled oak**

Oiled oak should be oiled twice a year for best protection. Good maintenance can never completely prevent stains from occurring, but oak that is not maintained will turn blacker and turn gray faster, but it still has a very long life. When re-oiling products, a finely boiled oil that penetrates the wood should be chosen over a film-forming oil. Black stains on oiled oak can be removed with oxalic acid.

### **Oiled mahogany**

Oiled mahogany should be oiled two times a year.

### **Powdercoated steel**

Products that are powder-coated can be touch-up painted with alkyd paint.

**Read more in our general maintenance advice at [nola.se/en/care-and-maintenance](https://nola.se/en/care-and-maintenance)**

## **Versions**

Teak on pine, oiled oak or FSC- mahogany.

## **Character**

Sjöstad provides additional support along the armrests and backrest, giving those who need assistance an independent means of sitting down and standing up.

## **Designers**

Erik  
Österlund



