

# nola®




## Standard Bike Rack

### Design Nola

Simple and sleek, Standard is a straightforward design consisting of a single metal unit where multiple bicycles can be securely fastened. The wheel-holders face forward so that bicycles wheels can slot into place in facing the rack. Locks, chains and steel cables can easily wind through the wheel-holders or attach to the base. Made of hot-dip galvanized steel, Standard is a durable outdoor design.

#### CERTIFICATION





#### Dimensions and weight

Length: 165 cm / 200 cm

Weight Ö03-11 module: 12 kg

Weight Ö03-13 module: 15 kg/ 19 kg

Weight Ö03-23 module: 14 kg

C-C wheel-holders Ö03-11 & Ö03-13V/R/H: 40 cm

C-C wheel-holders Ö03-22 (low wheel-holders): 40 cm

C-C wheel-holders Ö03-23 (compact version): 33 cm

#### Product numbers and combinations

Ö03-13H	Standard bike rack, 5 right-aligned wheel-holders, ground-mounted
Ö03-13R	Standard bike rack, 5 straight wheel-holders, ground-mounted
Ö03-13V	Standard bike rack, 5 left-aligned wheel-holders, ground-mounted
Ö03-19-4	Standard bike rack, 4 adjustable wheel-holders, ground-mounted
Ö03-19	Standard cykelställ 5 platser svetsade bågar, markfast.
Ö03-19-8	Standard cykelställ 8 platser dubbelsidigt bågar, markfast.
Ö03-19-10	Standard cykelställ 10 platser dubbelsidigt bågar, markfast.
Ö03-22	Standard bike rack, 5 low adjustable wheel-holders, freestanding
Ö03-23	Standard bike rack, 5 adjustable wheel-holders, freestanding
Ö03-23-6	Standard bike rack, 6 adjustable wheel-holders, freestanding
Ö03-23-10	Standard bike rack, 10 adjustable wheel-holders, freestanding
Ö03-18	Standard cykelställ 5 platser, väggfast, rak inkörning.

#### Append to product number

##### METAL SURFACE FINISH

C for stand any color other than standard, starting cost is added.

##### VARIANTS

V for left turn.

R for straight run-in.

H for right entry.

##### INSTALLATION TYPE

M for in-ground.

#### Standard colours



Hot-dip galvanized steel

#### Materials and surface treatments

### **Steel**

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

### **Hot-dip galvanized**

Hot-dip galvanizing provides very strong protection against corrosion. The steel is dipped into a bath of hot liquid zinc. The zinc attaches and creates a surface coating on the steel part, which is then taken out of the bath and drained of excess zinc.

### **Powder coating**

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

## **Assembly and placement**

### **Freestanding**

Freestanding product that is placed directly on the ground.

### **In-ground**

Cast in ground.

Model Ö 03-11 and model Ö 03-13 are delivered fully assembled. The other models are delivered in parts for assembly.

## **Maintenance**

### **Powdercoated steel**

Products that are powder-coated can be touch-up painted with alkyd paint.

### **Hot dip galvanized steel**

Hot-dip galvanized can be touch-up painted with so-called "cold galvanizing".

[Read more in our general maintenance advice at nola.se/en/care-and-maintenance](https://nola.se/en/care-and-maintenance)

## **Versions**

A choice of different models and sizes that can be powder-coated steel in non-standard colours for an additional fee.

## **Character**

Easy-access bike racks with different option, made of hot-dip galvanised steel.

## **Designers**

---

## **Nola**

---



Ö03-13R, markfast cykelställ med rak inbörning



Ö03-13R special pulverlackerad