# nola




## Tuben Armchair

### Design Gunilla Hedlund

Spring arrives to usher in warmer weather, bringing outdoor spaces to life. That's when Tuben's tables and chairs come out of winter storage and return to outdoor patios, central courtyards and roof terraces. The lightweight structure of these stackable designs makes them easy to transport and simple to store. The wooden slats form comfortable seats, while the tubular armrests recall the luxury of an outdoor recliner. Functional and fresh, Tuben bring contemporary style to any setting.

**CERTIFICATION** 

Produkt listad i Svanens Husportal ® BEDÖMNINGEN SSUNDAHUS



Dimensions and weight

Width: 70,5 cm Height: 65,5 cm Sitting height: 46 cm Depth: 67,5 cm Weight 15,5 kg

Product numbers and combinations

U20-84 Tuben armchair (only freestanding)

Append to product number

**VARIANTS** 

V for white. RAL 9010 on steel and NCS S 0502-Y on wood (White). G for green. RAL 6021 on steel and NCS S 3020-G20Y on wood (green). C for any color other than standard, starting cost is added.

Standard colours

RAL 9010
RAL 6021
NCS S 0502-Y (Vit)
NCS S 3020-G20Y (grön)

Materials and surface treatments

#### Pine

Nola's pine is of high quality and comes from sustainable forestry. Pine is an environmentally friendly, domestically produced material. Damaged or untreated pine is quite easily attacked by decomposition processes; therefore, it is particularly important to repair damaged surfaces.

#### **Topcoat**

Painted wood is made with D-Dur Pigmented Polyurethane two-component topcoat. The topcoat has good resistance and outdoor durability. Gloss number: 60.

#### Steel

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

#### Electrogalvanized

Electrogalvanizing (also known as zinc plating) provides corrosion protection through the sacrifice of zinc ions. It is created via a zinc coating on the steel using an electric current.

#### Powder coating

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

Assembly and placement

#### Freestanding

Freestanding product that is placed directly on the ground.

Fully assembled.

Maintenance

Glans 60. Pulverlack går att beställa på sprayflaska.

#### **Topcoat**

Products treated with D-Dur Pigmented polyurethane two-component topcoat should be maintained regularly. Maintenance intervals approx. 1 time per year. Damage and cracks should be repaired immediately. Touch-up paint with, for example, Nordsjö One door and window water-based topcoat.

#### Powdercoated steel

Products that are powder-coated can be touch-up painted with alkyd paint.

Read more in our general maintenance advice at nola.se/en/care-and-maintenance

Versions

The furniture group includes a bench, a backed bench a table and an armchair.

Character

Lightweight and stackable armchair with a tubular design.

Designers

Gunilla Hedlund









